



Charger

SICO 5007

The Charger SICO 5007 is used to exclusively charge Lithium-Ion accumulators of the type PA-LH201.K01.R001.

A diode glowing in different colours indicates the status of the charging cycle.

This product is recommended accessory for the following devices:

- [Tester for Insulated Rail Joints SICO 2046](#),
- [Service unit SICO 2056 PEGA](#), and
- [Selective Multimeter SICO 2061 KS](#)

Data

Mains voltage
- 90 ... 264 VAC
- 47 ... 63 Hz

Suitable battery type: Lithium-Ion, type PA-LH201.K01.R001

Storage temperature: -25 ... 85°C

Operation temperature: -25 ... 40°C

Protection degree: IP40

Protection class: II

Dimensions Battery box: 105 x 27 x 27 mm

Length cable: 1600 mm

Weight: 220 g

Delivery

- Charger SICO 5007
- Manual
- Acceptance test certificate 3.1 according to BS EN 10204



#241

Signal Concept GmbH
Geschäftsführer: Stefan Wetzig
Südring 11, 04416 Markkleeberg, Deutschland
Tel.: +49 (0)34297 1439 0, Fax: +49 (0)34297 1439 13

Seite 2/2 - 11.07.2026

Umsatzsteuer-ID gemäß § 27 a Umsatzsteuergesetz: DE155914966

E-Mail: info@signalconcept.de
Internet: www.signalconcept.de

