



Resistor Unit for Axle Resistance Measurement

SICO 1107

Quick and reliable measurements of the axle resistance in which the track circuit drops out (occupation of a line with shunting resistor)

Resistance settings: 0.1 | 0.2 | 0.3 | 0.4 | 0.5 | 0.6 | 0.7 | 0.8 | 0.9 | 1 Ohm

Data

Resistance settings: 0.1 | 0.2 | 0.3 | 0.4 | 0.5 | 0.6 | 0.7 | 0.8 | 0.9 | 1 Ohm

Frequency range: up to 30 kHz

Operating temperature range: -20°C to 55°C

IP code: IP 54

Dimensions: 80 x 160 x 60 mm

Weight: approx. 650g

Technology

The resistor unit for axle resistance measurement SICO 1107 can be used for acceptance/reconstruction tests and inspections of track circuits.

SICO 1107 permits quick and reliable measurements of the axle resistance in which the rail relay drops out.

The selection of the resistance by outlet socket ensures ease of use.

The Rail Clip Contact SZ 1103 is recommended for quick and secure installation of SICO 1107 on the rails.

Delivery

- Resistor SICO 1107
- Manual
- Acceptance test certificate 3.1 according BS EN 10204

Optional accessories

- Rail Clip Contact



